Hydraulic Grab Type Combi

The Combi grab series consists of a high quality hydraulic master unit which can be fitted with a wide range of different digging and clamping attachments. The ability to change attachments quickly and easily makes this grab one of the most flexible and useful in the BSV range.

Combi grabs are designed primarily for use with smaller hydraulic cranes, mini excavators, agricultural equipment, etc.

The Combi grab offers many advantages especially in terms of flexibility, durability and efficiency.

- Quick attachment change - no hand tool required
- The right tool for the right job
- High digging force for a small grab
- High torsion stability
- High quality 100% fully welded construction
- Produced in high grade steel
- Low unit weight
- Greaseable axles
- Minimal maintenance requirements

Flexibility

The impressive range of attachments makes the Combi hugely versatile.
Tools include open and close-sided bucket grabs, multi-purpose arms for manure, wood, compost and similar products as well as specialist arms for stacking, small trees, etc.

In addition to our standard range of attachments, we are also able to develop special tools for specific situations. Please contact us and we will provide you with further information.

Grab type Combi - G (Closed version)

Specification / type		120G	200G
Volume	Litre	120	200
Bucket width - closed (A)	mm.	950	950
Bucket width - open (B)	mm.	1.640	1.640
Length (C)	mm.	530	830
Height - open (D)	mm.	520	520
Height - closed (E)	mm.	800	800
Weight	kg.	140	160



Grab type Combi - GSX (Open version)

Specification / type		120 GSX	200 GSX
Volume	Litre	120	200
Bucket width - closed (A)	mm.	980	980
Bucket width - open (B)	mm.	1.670	1.670
Length (C)	mm.	530	830
Height - open (D)	mm.	510	510
Height - closed (E)	mm.	810	810
Weight	kg.	135	150



Grab type Combi - UNI

Multi-purpose / Manure arms

Specification / type		90 UNI	120 UNI
Volume	Litre	90	120
Bucket width - closed (A)	mm.	210	210
Bucket width - open (B)	mm.	1.220	1.220
Length (C)	mm.	760	1.010
Height - open (D)	mm.	690	690
Height - closed (E)	mm.	630	630
Weight	kg.	105	120



Grab type Combi - 0,2 M

Arms for stacking

Specification / type		0,2 M
Volume	Litre	0,2
Bucket width - closed (A)	mm.	180
Bucket width - open (B)	mm.	940
Length (C)	mm.	190
Height - open (D)	mm.	740
Height - closed (E)	mm.	560
Weight	kg.	83



MADE IN DENMARK

Agent