



TSZ Concrete Step Handles

Suitable for handling steps, kerb stones etc. in conjunction with a lifting device.

- Easily adjustable opening width by means of a spring-loaded bolt.
- Considerable inside height. Conical kerb stones are also gripped securely, as the gripper has an inside height of 185 mm (7¼ inch) thus being able to grip underneath the conical form.
- Lifting eye for attaching to crane hook.
- Automatic release for fully automatic switch-over from "full" to "empty".
- Exchangeable profiled rubber seals.
- Setting the gripping range for TSZ-UNI-800 via scale.
- Galvanised finish.

TSZ-UNI-800 with HVA-FTZ/TSZ (black)

Type	Working Load Limit/WLL kg (lbs)	Dead Weight kg (lbs)	Gripping Range mm (in)	Length of Gripper mm (in)	Inside Height mm (in)	Order-Number
TSZ- UNI- 800	800 (1,764)	31 (68)	50 – 600 (1.97 – 23.62)	350 (13.78)	185 (7.28)	53100451
TSZ- MAXI- 800	800 (1,764)	35 (77)	850 – 1,100 (33.46 – 43.31)	350 (13.78)	185 (7.28)	53100453

Accessories:



HVA-FTZ/TSZ (black)

TSZ-UNI-WB-SQ

HVA- FTZ/ TSZ (black) / HVA- FTZ/ TSZ (grey): for all versions of FTZ-UNI/MAXI/MULTI and TSZ-UNI. Black rubber. Adjustable range TSZ-UNI/MAXI

approx. 55 – 140 mm (2¼ – 5½ inch). Adjustable range FTZ-UNI/MAXI-25 and FTZ-UNI/MULTI-15 approx. 120 – 255 mm (4¾ – 10 inch).

FTZ-UNI-50 approx. 55 – 155 mm (2¼ – 6¼ inch). FTZ-MAXI-50 approx. 55 – 195 mm (2¼ – 7¾ inch).

TSZ- UNI- WB- SQ: Special steelfinger grippers allow for safe installation of roughly-cut ashlar rocks. The steel-finger grippers can be screwed on the clamp

in just a few simple steps.

Type	Description	Dead Weight kg (lbs)	Gripping Range mm (in)	Inside Height mm (in)	Length of Gripper mm (in)	Order-Number
HVA- FTZ/ TSZ (black)	Adjustable Height Stop (Black rubber)	2.5 (5.51)				43100867
HVA- FTZ/ TSZ (grey)	Adjustable Height Stop (Grey rubber)	2.9 (6.39)				43100867-003
Rubber strip profile, grey		0.4 (0.88)			350(13.78)	36370030
TSZ- UNI- WB- SQ	Steelfinger grippers	5.6 (12)	50-550 (1.97-21.65)	210(8.27)		43101384